

Drewelow Remediation Equipment, Inc.

A CERTIFIED SMALL BUSINESS ENTERPRISE
WWW.DRE-EQUIP.COM

SRCO-250E Data Sheet

Equipment description – Catalytic Combustion SRCO 250E is a 250 scfm all electric catalytic oxidizer. gas/liquid separator with auto drain, Sutorbilt 4L positive displacement blower, 10hp electric motor, v-belt drive, exhaust silencer, SCH 40 carbon steel piping, 250 scfm electric catalytic oxidizing chamber with two stage catalyst designed for 99% DRE, exhaust stack, skid mounted. NEMA 4 UL listed control panel. Honeywell 3 pen chart recorder.

| | | | |
|-------------------------------------|---|------------------------------|-----------------------------------|
| Model number | SRCO-250E | Serial number | |
| Maximum air flow capacity | 250 scfm | Maximum blower vacuum | 10 in hg. |
| Influent process connections | 3 inch NPT | Exhaust stack | 6 inch diameter |
| Electrical requirements | 230 volt single phase 230 volt three phase | Sub panel amp rating | 200 amps, install 200 amp breaker |

Equipment Dimensions

| | | | |
|---------------|-----------------|---------------------|---------|
| Length | 8 feet | Width | 6 feet |
| Height | 6 feet 2 inches | Stack height | 12 feet |

